

THREE-PHASE HYBRID INVERTER

HIT Series



Features

- 01 4 MPPTs with 20 A input; DC/AC oversizing up to 200%
- 02 100% unbalanced output; max. output of each phase up to 50% rated power
- 03 Support multiple intelligent operating modes, including Peak Shaving and up to eight configurable 24-hour TOU schedules
- 04 Integrated AI energy management with generator, heat pump and smart load
- 05 Max. 10 inverters in parallel for on-grid and off-grid system extension
- 06 Ultralight for easy installation and space-saving; unique built-in meter solution with up to 50 A bypass

Technical Specifications

Model	HIT-5L-G3/ HIT-5L-G3S	HIT-6L-G3/ HIT-6L-G3S	HIT-8L-G3/ HIT-8L-G3S	HIT-10L-G3/ HIT-10L-G3S	HIT-12L-G3/ HIT-12L-G3S	HIT-15L-G3/ HIT-15L-G3S	HIT-17L-G3/ HIT-17L-G3S	HIT-20L-G3/ HIT-20L-G3S	
Battery									
Battery type	Li-ion/Lead-acid								
Battery voltage range (V)	40-60								
Max. charge/discharge current (A)	120/120	150/150	190/190	210/210	250/250	300/300	350/350	350/350	
Charging strategy for Li-ion battery	Self-adaption to BMS								
Charging curve	3 Stages/Equalization								
External temperature sensor	Optional								
Communication	CAN								
PV Input									
Recommended max. PV power (W)	10000	12000	16000	20000	24000	30000	34000	40000	
Max. input voltage (V)	1000								
Rated voltage (V)	720								
Start-up voltage (V)	150								
MPPT voltage range (V)	150-900								
Max. input current (A)	20/20	20/20	20/20/20	20/20/20	20/20/20/20	20/20/20/20	20/20/20/20	20/20/20/20	
Max. short circuit current (A)	30/30	30/30	30/30/30	30/30/30	30/30/30/30	30/30/30/30	30/30/30/30	30/30/30/30	
MPPT number/Max. input strings number	2/2	2/2	3/3	3/3	4/4	4/4	4/4	4/4	
AC Input and Output (On-grid)									
Rated output power (W)	5000	6000	8000	10000	12000	15000	17000	20000	
Max. output apparent power (VA) ⁽¹⁾	5500	6600	8800	11000	13200	16500	18700	22000	
Grid form	3L/N/PE								
Rated AC output voltage/Range (V)	380/400, 266-480								
Rated grid frequency (Hz)	50/60								
Rated output current (A)	7.2	8.7	11.5	14.4	17.3	21.7	24.5	28.9	
Max. output current (A)	8.3	10	13.3	16.7	20	25	28.3	33.3	
Power factor	>0.99 (0.8 leading ... 0.8 lagging)								
THDi (@rated output)	<3%								
AC Output (Back-up)									
Rated output power (W)	5000	6000	8000	10000	12000	15000	17000	20000	
Max. output apparent power (VA) ⁽²⁾	10000, 10s	12000, 10s	16000, 10s	20000, 10s	24000, 10s	30000, 10s	34000, 10s	40000, 10s	
Back-up switch time (ms)	<10								
Grid form	3L/N/PE								
Rated output voltage (V)	380/400								
Rated output frequency (Hz)	50/60								
Max. continuous output current (A)	7.6	9.1	12.2	15.2	18.2	22.8	25.8	30.4	
Max. continuous AC bypass current (A)	50								
THDv (@linear load)	<3%								
Efficiency									
MPPT efficiency					99.9%				
Max. efficiency	98.2%				98.5%				
EU efficiency	97.6%				98.0%				
Max. battery discharge to AC efficiency					95.7%				
Protection									
Anti-islanding protection					Integrated				
PV string input reverse polarity protection					Integrated				
Insulation resistor detection					Integrated				
Residual current monitoring unit					Integrated				
AC overcurrent protection					Integrated				
AC short current protection					Integrated				
AC overvoltage and undervoltage protection					Integrated				
AFCI					Optional				
Surge protection					DC Type II/AC Type II				
General									
Dimensions (W × H × D [mm]) ⁽³⁾					539 × 696 × 232				
Weight (kg)					41				
Mounting					Wall mounting				
Operating temperature (°C)					-25 to +65 (>45, derating)				
Relative humidity					0-95%, no condensing				
Cooling	Natural convection				Smart fan				
Topology (Solar/Battery)					Transformerless/High-frequency isolation				
Altitude (m)					≤4000 (>2000, derating)				
Protection degree					IP66				
Noise (dB)	<45				<60				
User interface					App, LED, LCD (Optional)				
Digital input/output					DRM, 2 × DI, 2 × DO				
Communication					RS485, Wi-Fi/Ethernet/4G (optional) ⁽⁴⁾				
Certifications and Standards									
Grid connection standard	IEC 61727, IEC 62116, EN 50549, VDE-AR-N 4105								
Safety/EMC standard	IEC 62109-1/-2, EN 61000-6-1/-2/-3/-4								

(1) For Belgium, the maximum output apparent power is equal to the nominal output apparent power.

(2) Can be achieved only if PV and battery power are sufficient.

(3) Excluding Connectors and Brackets.

(4) The DTS-4G solution will be coming soon.