



MAAN SOLAR TRADERS

AUTHORIZED DISTRIBUTOR OF



THREE-PHASE HYBRID INVERTER

HIT Series



Features

- 4 MPPTs with 20 A input; DC/AC oversizing up to 200%
- 100% unbalanced output; max. output of each phase up to 50% rated power
- Support multiple intelligent operating modes, including Peak Shaving and up to eight configurable 24-hour TOU schedules
- Integrated AI energy management with generator, heat pump and smart load
- Max. 10 inverters in parallel for on-grid and off-grid system extension
- Ultralight for easy installation and space-saving; unique built-in meter solution with up to 50 A bypass



MAAN SOLAR TRADERS

Web:
maansolartraders.com

Email:
info@maansolartraders.com

Phone:
+92 302 5074026

Address:
Shop#3, Jamshaid Arcade, MPS Road, Multan

Technical Specifications

Model	HIT-5L-G3 / HIT-5L-G3S	HIT-6L-G3 / HIT-6L-G3S	HIT-8L-G3 / HIT-8L-G3S	HIT-10L-G3 / HIT-10L-G3S	HIT-12L-G3 / HIT-12L-G3S	HIT-15L-G3 / HIT-15L-G3S	HIT-17L-G3 / HIT-17L-G3S	HIT-20L-G3 / HIT-20L-G3S
Battery								
Battery type	Li-ion / Lead-acid							
Battery voltage range (V)	40-60							
Max. charge/discharge current (A)	120/120	150/150	190/190	210/210	250/250	300/300	350/350	350/350
Charging strategy for Li-ion battery	Self-adaption to BMS							
Charging curve	3 Stages / Equalization							
External temperature sensor	Optional							
Communication	CAN							
PV Input								
Recommended max. PV power (W)	10000	12000	16000	20000	24000	30000	34000	40000
Max. input voltage (V)	1000							
Rated voltage (V)	720							
Start-up voltage (V)	150							
MPPT voltage range (V)	150-900							
Max. input current (A)	20/20	20/20	20/20/20	20/20/20	20/20/20/20	20/20/20/20	20/20/20/20	20/20/20/20
Max. short circuit current (A)	30/30	30/30	30/30/30	30/30/30	30/30/30/30	30/30/30/30	30/30/30/30	30/30/30/30
MPPT number / Max. input strings number	2/2	2/2	3/3	3/3	4/4	4/4	4/4	4/4
AC Input and Output (On-grid)								
Rated output power (W)	5000	6000	8000	10000	12000	15000	17000	20000
Max. output apparent power (VA) (1)	5500	6600	8800	11000	13200	16500	18700	22000
Grid form	3L/N/PE							
Rated AC output voltage/Range (V)	380/400, 266-480							
Rated grid frequency (Hz)	50/60							
Rated output current (A)	7.2	8.7	11.5	14.4	17.3	21.7	24.5	28.9
Max. output current (A)	8.3	10	13.3	16.7	20	25	28.3	33.3
Power factor	>0.99 (0.8 leading ... 0.8 lagging)							
THDi (@rated output)	<3%							
AC Output (Back-up)								
Rated output power (W)	5000	6000	8000	10000	12000	15000	17000	20000
Max. output apparent power (VA) (2)	10000,10s	12000,10s	16000,10s	20000,10s	24000,10s	30000,10s	34000,10s	40000,10s
Back-up switch time (ms)	<10							
Grid form	3L/N/PE							
Rated output voltage (V)	380/400							
Rated output frequency (Hz)	50/60							
Max. continuous output current (A)	7.6	9.1	12.2	15.2	18.2	22.8	25.8	30.4
Max. continuous AC bypass current (A)	50							
THDv (@linear load)	<3%							

Model	HIT-5L-G3 / HIT-5L-G3S	HIT-6L-G3 / HIT-6L-G3S	HIT-8L-G3 / HIT-8L-G3S	HIT-10L-G3 / HIT-10L-G3S	HIT-12L-G3 / HIT-12L-G3S	HIT-15L-G3 / HIT-15L-G3S	HIT-17L-G3 / HIT-17L-G3S	HIT-20L-G3 / HIT-20L-G3S
Efficiency								
MPPT efficiency	99.9%							
Max. efficiency	98.2%	98.2%	98.2%	98.2%	98.5%	98.5%	98.5%	98.5%
EU efficiency	97.6%	97.6%	97.6%	97.6%	98.0%	98.0%	98.0%	98.0%
Max. battery discharge to AC efficiency	95.7%							
Protection								
Anti-islanding protection	Integrated							
PV string input reverse polarity protection	Integrated							
Insulation resistor detection	Integrated							
Residual current monitoring unit	Integrated							
AC overcurrent protection	Integrated							
AC short current protection	Integrated							
AC overvoltage and undervoltage protection	Integrated							
AFCI	Optional							
Surge protection	DC Type II / AC Type II							
General								
Dimensions (W × H × D [mm]) (3)	539 × 696 × 232							
Weight (kg)	41							
Mounting	Wall mounting							
Operating temperature (°C)	-25 to +65 (>45, derating)							
Relative humidity	0-95%, no condensing							
Cooling	Natural convection	Natural convection	Smart fan	Smart fan	Smart fan	Smart fan	Smart fan	Smart fan
Topology (Solar/Battery)	Transformerless / High-frequency isolation							
Altitude (m)	≤4000 (>2000, derating)							
Protection degree	IP66							
Noise (dB)	<45	<45	<60	<60	<60	<60	<60	<60
User interface	App, LED, LCD (Optional)							
Digital input/output	DRM, 2 × DI, 2 × DO							
Communication	RS485, Wi-Fi/Ethernet/4G (optional) (4)							
Certifications and Standards								
Grid connection standard	IEC 61727, IEC 62116, EN 50549, VDE-AR-N 4105							
Safety/EMC standard	IEC 62109-1/-2, EN 61000-6-1/-2/-3/-4							

(1) For Belgium, the maximum output apparent power is equal to the nominal output apparent power.

(2) Can be achieved only if PV and battery power are sufficient.

(3) Excluding connectors and brackets.

(4) The DTS-4G solution will be coming soon.